

| OLIVEIAL               |                                                                   |
|------------------------|-------------------------------------------------------------------|
| Credential Support     | Fingerprint, RF Card, PIN and Bluetooth                           |
| IK Rating              | IK06 (Complies IEC 62262 Standard)                                |
| IP Rating              | IP65 (Complies IEC 60529 Standard)                                |
| RF Option              | EM Prox Card Support (Inbuilt)                                    |
|                        |                                                                   |
| DISPLAY                |                                                                   |
| Display                | 3.5" IPS Display with Capacitive Touch Panel with Gorilla Glass 3 |
| Display resolution     | 480 X 320 Pixel (HVGA)                                            |
|                        |                                                                   |
| CAPACITY               |                                                                   |
| Max. Users             | 50,000                                                            |
| Max. Template Storage  | 25,000 in 1: N Mode and 100,000 in 1:1 Mode                       |
| Event Buffer           | 500,000 Events                                                    |
| Templates per User     | Up to 10 (Single Template per Finger Mode)                        |
|                        | Up to 5 (Dual Template per Finger Mode)                           |
| COMMUNICATION          |                                                                   |
| Wi-Fi                  | Yes (IEEE 802.11 b/g/n)                                           |
| Ethernet               | Yes (10/100 Mbps)                                                 |
| PoE                    | Yes (IEEE 802.3 af)                                               |
| RS-232                 | Yes                                                               |
| Mobile Connectivity    | Yes (3G/4G/LTE)                                                   |
| Wiegand                | Wiegand IN/OUT Available                                          |
| USB                    | 1 Micro-USB Port (Data Transfer and 2G-3G Dongle)                 |
| Bluetooth              | Yes, Built-in (8m Range)                                          |
| INTERFACE              |                                                                   |
| Exit Switch Port       | Yes                                                               |
| Door Status Sense      | Yes                                                               |
| Door Lock Relay        | 30V DC @ 2 A, Form C, DPDT Relay                                  |
|                        | 12V DC @ 0.5A (Power to external Lock from Device)                |
| Door Lock Power        | 30V DC @2 A (Power to lock from External power source)            |
|                        | Set De e 27() ower to lock nom External power source)             |
|                        |                                                                   |
| Reader Interface Types | RS-232 and Wiegand IN/OUT                                         |
|                        |                                                                   |

| HARDWARE                            |                                                          |
|-------------------------------------|----------------------------------------------------------|
| OS                                  | Embedded LINUX                                           |
| CPU                                 | 800 MHz ARM Cortex A8 Based Processor                    |
| Memory                              | 512 MB Flash + 512 MB DDR3 RAM                           |
| Mounting Options                    | Wall Mounting, Flush Mounting                            |
| Tamper Detection                    | Yes                                                      |
| Power                               | 12V DC @ 2A                                              |
| Dimensions                          | Wall Mount:186mm(H) x 74mm(W) x 50mm(D)                  |
| Dimensions                          | Flush Mount: 186mm(H) x 74mm(W) x 16mm(D)                |
| Weight                              | 0.550 Kgs                                                |
|                                     |                                                          |
| AUDIO-VISUAL                        |                                                          |
| User Photo Display                  | Yes                                                      |
| Buzzer                              | Yes                                                      |
| COMPATIBILITY                       |                                                          |
| System Integration                  | API for Software Integration                             |
|                                     | Direct Door with COSEC CENTRA / COSEC VYOM               |
| Operational Modes                   | Panel Door with COSEC PANEL200P                          |
|                                     |                                                          |
| SENSOR                              |                                                          |
| Sensor Name                         | Suprema Optical Sensor – SFM6030                         |
| Sensor Technology                   | Optical Technology                                       |
| Encryption                          | 256-bit AES                                              |
| EER                                 | <0.08%                                                   |
| Resolution (dpi)                    | 500                                                      |
| Sensing Area                        | 16.0mm x 18.0mm                                          |
| Template Size<br>Image Size (Pixel) | 384 bytes<br>288 x 288                                   |
| lillage Size (Pixel)                | 200 X 200                                                |
| ENVIRONMENTAL                       |                                                          |
| Operating Temperature               | 0°C to +50°C                                             |
| Humidity                            | 5% to 95% RH Non – Condensing                            |
| Thermal Sensor                      | Yes, Built-in to Indicate Overheat Conditions            |
|                                     |                                                          |
| CERTIFICATIONS                      | Cartifications: CE, DIC, ECC, and LU                     |
|                                     | Certifications: CE, BIS, FCC, and UL<br>Compliance: RoHS |
|                                     | compliance. Nons                                         |
| APPLICATIONS                        |                                                          |
|                                     | Access Control                                           |
|                                     | Time-Attendance                                          |
|                                     | Visitor Management                                       |
|                                     | Contract Workers Management                              |
|                                     | Cafeteria Management                                     |
|                                     | Job Processing and Costing                               |
|                                     |                                                          |

\*Due to continuous technology upgradations, product specifications are subject to change without notice.

### **ABOUT MATRIX**

Established in 1991, Matrix is a leader in Security and Telecom solutions for modern organizations. Matrix offers a comprehensive range of solutions for IP Video Surveillance, Access Control, Time-Attendance, and Telecom applications. The solutions are designed to meet the communication and security requirements of large enterprises having offices in multiple locations, SMEs, and SMBs.

As an innovative, technology-driven, and customer-focused organization, Matrix is committed to keeping pace with the revolutions in the Security and Telecom industries. With around 40% of its human resources dedicated to the development of new products, Matrix has launched over 60 cutting-edge products and solutions.

IP Video Surveillance includes solutions like Video Management Systems, Network Video Recorders, and IP Cameras. Likewise, solutions in Access Control and Time-Attendance include Visitor Management Solutions, Elevator Access Control, Panels, Door Controllers, and Readers.

We offer Telecom Solutions such as Unified Communications, IP-PBX, Universal Media Gateways, VoIP and GSM Gateways, and Communication Endpoints. All these solutions are feature-rich, reliable, and conform to international standards.



# MATRIX COMSEC

## **Head Office**

394-GIDC, Makarpura, Vadodara-390 010, India. Ph: (+91) 265-613-7222 E-mail: Inquiry@MatrixComSec.com

### Factory

19-GIDC, Waghodia, Dist. Vadodara-391 760, India. Ph: (+91) 265-613-7222

## **MATRIX COMSEC - North America**

2 Wickstead Crt, Brampton, Ontario, L6R 1N8. +1 408-643-0581 (USA) +1 437-266-1005 (Canada)

www.MatrixAccessControl.com