

GENERAL

Credential Support

IK Rating

IK Rating

IF Rating

IF Roption

Fingerprint, RF Card, PIN and Bluetooth

IK Romplies IEC 62262 Standard)

IP 65 (Complies IEC 60529 Standard)

Mifare Card Support (Inbuilt)

Read and Write Mifare Card Type

DISPLAY

Display 3.5" IPS Display with Capacitive Touch Panel with Gorilla Glass 3

Display resolution 480 X 320 Pixel (HVGA)

CAPACITY

Max. Users 50,000

Max. Template Storage 25,000 in 1: N Mode and 100,000 in 1:1 Mode

Event Buffer 500,000 Events

Templates per User

Up to 10 (Single Template per Finger Mode)

Up to 5 (Dual Template per Finger Mode)

COMMUNICATION

 Wi-Fi
 Yes (IEEE 802.11 b/g/n)

 Ethernet
 Yes (10/100 Mbps)

 PoE
 Yes (IEEE 802.3 af)

RS-232 Yes

Mobile Connectivity Yes (3G/4G/LTE)

Wiegand IN/OUT Available

USB 1 Micro-USB Port (Data Transfer and 2G-3G Dongle)

Bluetooth Yes, Built-in (8m Range)

INTERFACE

Exit Switch Port Yes
Door Status Sense Yes

Door Lock Relay 30V DC @ 2 A, Form C, SPDT Relay

12V DC @ 0.5A (Power to external Lock from Device)

Door Lock Power 30V DC @2 A (Power to lock from External power source)

Reader Interface Types RS-232, and Wiegand IN/OUT

HARDWARE

OS Embedded LINUX

CPU 800 MHz ARM Cortex A8 Based Processor
Memory 512 MB Flash + 512 MB DDR3 RAM
Mounting Options Wall Mounting, Flush Mounting

Tamper Detection Yes

Power 12V DC @ 2A

Dimensions Wall Mount:186mm(H) x 74mm(W) x 50mm(D) Flush Mount: 186mm(H) x 74mm(W) x 16mm(D)

Weight 0.550 Kgs

AUDIO-VISUAL

User Photo Display Yes Buzzer Yes

COMPATIBILITY

Operational Modes

System Integration API for Software Integration

Direct Door with COSEC CENTRA / COSEC VYOM

Panel Door with COSEC PANEL200P

SENSOR

Sensor Name Suprema Optical Sensor – SFM6030

Sensor Technology Optical Technology

Encryption 256-bit AES
EER <0.08%
Resolution (dpi) 500

Sensing Area 16.0mm x 18.0mm

Template Size 384 bytes Image Size (Pixel) 288 x 288

ENVIRONMENTAL

Operating Temperature 0°C to +50°C

Humidity 5% to 95% RH Non – Condensing

Thermal Sensor Yes, Built-in to Indicate Over Heat Conditions

CERTIFICATIONS

Certifications: CE, BIS, FCC, and UL

Compliance: RoHS

APPLICATIONS

Access Control
Time-Attendance
Visitor Management

Contract Workers Management

Cafeteria Management

Job Processing and Costing

^{*}Due to continuous technology upgradations, product specifications are subject to change without notice.

ABOUT MATRIX

Established in 1991, Matrix is a leader in Security and Telecom solutions for modern organizations. Matrix offers a comprehensive range of solutions for IP Video Surveillance, Access Control, Time-Attendance, and Telecom applications. The solutions are designed to meet the communication and security requirements of large enterprises having offices in multiple locations, SMEs, and SMBs.

As an innovative, technology-driven, and customer-focused organization, Matrix is committed to keeping pace with the revolutions in the Security and Telecom industries. With around 40% of its human resources dedicated to the development of new products, Matrix has launched over 60 cutting-edge products and solutions.

IP Video Surveillance includes solutions like Video Management Systems, Network Video Recorders, and IP Cameras. Likewise, solutions in Access Control and Time-Attendance include Visitor Management Solutions, Elevator Access Control, Panels, Door Controllers, and Readers.

We offer Telecom Solutions such as Unified Communications, IP-PBX, Universal Media Gateways, VoIP and GSM Gateways, and Communication Endpoints. All these solutions are feature-rich, reliable, and conform to international standards.



MATRIX COMSEC

Head Office

394-GIDC, Makarpura, Vadodara-390 010, India.

Ph: (+91) 265-613-7222

E-mail: Inquiry@MatrixComSec.com

Factory

19-GIDC, Waghodia, Dist. Vadodara-391 760, India.

Ph: (+91) 265-613-7222

MATRIX COMSEC - North America

2 Wickstead Crt, Brampton, Ontario, L6R 1N8. +1 408-643-0581 (USA) +1 437-266-1005 (Canada)

www.MatrixAccessControl.com