2MP IR Ruggedized Camera with 2.8mm Lens





Matrix Ruggedized Series IP Cameras are specifically designed for the demanding Transportation industry, i.e. Railways and Roadways. Powered by Low light Sensitivity and High quantum efficiency Sensor they offer superior Video Quality and performance necessary to capture events happening at a zap speed in/from a moving vehicle.

The Ruggedized IP Cameras are best suited for mobile applications. Loaded with versatile functions and a range of features, Matrix Ruggedized IP Cameras are an ideal Solution for Railways and Roadways to monitor assets.

### **USP**



SONY STARVIS SENSOR



H.265 COMPRESSION



IVA



HIGHER FIELD OF VIEW



SMART STREAMING



ADAPTIVE STREAMING



TRUE WDR



NAS

#### **CERTIFICATION**


















2MP IR Ruggedized Camera with 2.8mm Lens



TECHNICAL SPECIFICATIONS IMAGE SENSOR		
	1/2.8" SONY - CMOS 2MP Active Pixel	
Sensor Type and Size	Progressive Scan, Back Illuminated Image sensor (STARVIS Series)	
71	LENS	
	Color - 0.01 Lux @ F1.2 (AGC ON)	
Minimum Illumination	Monochrome - 0 Lux	
Focal Length	2.8mm	
Focus Range	0.5m to infinity	
	HFOV - 107°	
	VFOV - 61° DFOV - 132°	
Field of View (FOV)	DFOV - 132	
Lens Mount	M12/M16	
Focus	Fixed focus	
Aperture (F#)	F 1.2 / F 1.6 / F 1.8 / F 2.0	
Iris Type	Fixed	
IR Range	Up to 30m	
IR Led Wavelength	850nm	
IR Switching	Auto/ Manual	
HARDWARE SPECIFICATIONS		
SD Card	Up to 512GB	
Camera Adjustment Angle	Pan: -30° to 30°	
	Tilt: 10° to 90°	
	Rotate: -175° to 175°	
IMAGE AND VIDEO		
No of Stream Profiles	4	
	Four streams support	
	Profile 1:- 1080p(2MP)/720p/D1/VGA/2CIF/CIF/QCIF upto 60 fps(H.265/H.264)	
Stream Profiles	Profile 2:- D1/2CIF/CIF/QCIF upto 30fps(H.265/H.264)	
Stream Fromes	Profile 3:- 1080p(2MP)/720p/D1/2CIF/CIF/QCIF/VGA upto 5 fps(MJPEG)	
	Profile 4:- 720p/D1/2CIF/VGA/CIF/QCIF upto 30 fps(H.265/H.264)	
Available Resolutions	1920 x 1080, 720p,D1,2CIF,CIF,QCIF,VGA	
Max Resolution	1920 x 1080	
Bitrate	32 kbps-8Mbps	
Bitrate Type	CBR, VBR	
Video Compression	H.265, H.264, MJPEG	
Frame Rate	1-60fps	
Shutter Speed	1/50000-1 sec	





zivir in nuggeuizeu Cairiera i	With 2.8him Lens IELECUM   SECURI
Adaptive Streaming	Yes
ONVIF Profiles	Profile S and G
Edge Recording	Yes (Only in NAS)
Alarm Recording	Pre and Post
Motion Recording	Yes
Video Parameters	Snapshot, Region of Interest (ROI), BLC, Day/Night Settings
Privacy Masks	3
WDR	True WDR (120dB)
SNR	>70dB
Image Enhancement	Saturation/ Contrast/ Sharpness/Brightness/Auto Exposure
DNR	2D &3D
	Motion/No Motion Detection, Tamper Detection, Trip/No Trip
Video Analytics	Detection, Object Intrusion/Zone Intrusion, Loitering,
	Missing/Abandoned object
	ALERTS
IP Conflict	Yes
Network Disconnect	Yes
Storage Full	Yes
Time Triggered	Yes
	EVENTS AND ACTIONS
Upload Image	SD, NAS, SFTP, SSFTP, HTTP
Upload Clip	SD, NAS, SFTP, SSFTP, HTTP
Notifications	E-mail, SMS, TCP, HTTP, SNMP trap
	PROTOCOLS SUPPORTED
Supported protocols	IPv4, HTTP, SSL\TLS, Qos Layer 3, DiffServ, SFTP, Bonjour, UPnP, SNMP, v1/v2c/v3, DNS, DynDNS, NTP,RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SSH
Web Viewer	Supported in IE 8.0-11.0, Firefox 15.0-47.0, Chrome 20.0-54.0, Safari
Browser	IE, Chrome, Mozilla, Edge, Safari
	OPERATING PARAMETERS
Power Supply	12V (DC); 802.3af (PoE)
Power Consumption	Maximum 7W
Operating Humidity	Less than 95% RH (non-condensing)
Operating Temperature	-30°C to 70°C
Storage Temperature	-40°C to 80°C
	CYBER SECURITY
Secure boot	Yes
Signed firmware	Yes
Data Encryption	All data, including sensitive data, is encrypted with AES 256 and RSA 2048

## 2MP IR Ruggedized Camera with 2.8mm Lens



IP Address Filtering	Yes	
HTTPS Streaming	Yes, using TLS 2.0	
Edge Data Encryption	Yes	
Network Authentication	Yes, 802.1x Network authentication	
Secure Firmware Upgrade	Yes	
Anti-roll back firmware	Yes	
Web login Password Protection	Yes	
Unused Debug Interface Protection	Yes	
PHYSICAL PARAMETERS		
Communication interface	10Base-T/100BaseTX Ethernet (RJ-45)	
Weight	600g	
Color	Infinity White	
Dimensions	120x120x40 mm	
Certifications	BIS, CE, IP67, FCC Part-15 Subpart – B, IK10, UL, NEMA 4X, EN50155	

<sup>\*</sup>Specifications are subject to change without prior notice

2MP IR Ruggedized Camera with 2.8mm Lens



#### **ABOUT MATRIX**

Established in 1991, Matrix is a leader in security and telecom solutions for modern businesses and enterprises. Matrix, an innovative, technology driven and customer focused organization, is committed to keep pace with the revolutions in security and telecom industries. With more than 40% of its human resources dedicated to the development of new products, Matrix has launched cutting-edge products such as Unified Communications, IP-PBX, Universal Gateways, Convergence, VOIP Gateways, GSM Gateways, IP Video Surveillance, Access Control and Time-Attendance. These solutions are feature-rich, reliable and conform to the international standards. Having global footprints in Europe, North America, South America, Africa and Asia through an extensive network of more than 1000 system integrators, Matrix ensures that the products serve the needs of its customers faster and longer. Matrix has gained trust and admiration of customers representing the entire spectrum of industries. Matrix has won many national and international awards for its innovative products.



#### MATRIX COMSEC

Head Office 394-GIDC, Makarpura, Vadodara – 390 010, India.

Ph: +91 265 613 7222

E-mail: Inquiry@MatrixComSec.com

Factory

19 – GIDC, Waghodia,

Dist. Vadodara – 391 760, India.

Ph: +91 265 613 7222

MATRIX COMSEC - North America

2 Wickstead Crt, Brampton, Ontario, L6R 1N8.

Ph: (+1) 408-643-0581 (USA) Ph: (+1) 437-266-1005 (Canada)

www.MatrixComSec.com